

XL GRIP PLUS - Especificaciones técnicas



Description

XL GRIP PLUS (L-4) ha sido específicamente desarrollado para utilizarlo en las palas cargadoras. Su profunda banda de rodadura asegura una óptima resistencia a los cortes y las perforaciones, así como un ciclo de vida prolongado del neumático. XL GRIP PLUS es particularmente idóneo para condiciones de trabajo pesadas.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Buldócer • Pala cargadora

Version	STANDARD
Type	TL
Tyre Size	29.5 - 25

Dimensions US Standard

Usa code	94044863
Ply Rating	32
Overall Width (inch)	29.9
Overall Diameter (inch)	75.4
Static Loaded Radius (inch)	34.5
Rolling Circumference (inch)	224.8
Rim Rec	25.00/3.5
TRA Code	L4

Load capacity (lbs)

mph / psi	73
5	42440

Printed on 19/05/2024 0:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..