

## XL GRIP PLUS - Especificaciones técnicas



### Description

XL GRIP PLUS (L-4) ha sido específicamente desarrollado para utilizarlo en las palas cargadoras. Su profunda banda de rodadura asegura una óptima resistencia a los cortes y las perforaciones, así como un ciclo de vida prolongado del neumático. XL GRIP PLUS es particularmente idóneo para condiciones de trabajo pesadas.

### UM

US Standard

### Construction

 BIAS

### Machinery

OTR: Buldócer • Pala cargadora

Version	STANDARD
Type	TL
Tyre Size	35/65 - 33

## Dimensions US Standard

Usa code	94064762
Ply Rating	42
Overall Width (inch)	35.4
Overall Diameter (inch)	81.9
Rim Rec	28.00/3.5
TRA Code	L4

## Load capacity (lbs)

mph / psi	91
5	58400

Printed on 18/05/2024 17:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..