

AGRIMAX FORCE - Spécifications techniques



Description

AGRIMAX FORCE, le produit phare de BKT, est un pneu radial spécialement conçu pour les applications de traitement du terrain, de transport et de récolte avec des tracteurs de grande puissance, auxquels il assure un maximum de performances et d'efficacité. Conçu avec la technologie IF, ce pneu supporte des charges lourdes avec de pressions de gonflage plus basses par rapport à un pneu standard. AGRIMAX FORCE se distingue de par une tringle renforcée en assurant une traction excellente, des excellentes qualités d'autonettoyage, une consommation réduite de carburant ainsi qu'une expérience confortable de conduite.;

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Moissonneuse • Tracteur de forte puissance

Version	STANDARD
Type	TL
Tyre Size	IF 800/70 R 42 CFO
LI/SS	192 D

Dimensions International Standard

Section Width (mm)	794
Overall Diameter (mm)	2150
Static Loaded Radius (mm)	950
Rolling Circumference (mm)	6400
SRI (mm)	1025
Rim Rec	DW 27 B
Rim Alt	DW 25 B, DW 28 B, DW 30 B
ECE	E11-106R-006481
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
70	3980	4690	5405	6020	6730	7345	8055	8670	9485	10195
from 65 to 40	4370	5155	5940	6610	7395	8065	8850	9520	10420	11200
30	4545	5360	6175	6875	7690	8390	9205	9905	10835	11650
20	4720	5570	6415	7140	7990	8715	9560	10285	11255	12100
10	5550	6545	7540	8395	9390	10245	11240	12095	13230	14225
Upto 30 Cyc	5680	6700	7720	8595	9610	10485	11505	12380	13545	14560
Upto 15 Cyc	6775	7990	9205	10245	11460	12500	13715	14760	16145	17360
Upto 10 Cyc	7430	8760	10095	11235	12570	13710	15045	16185	17710	19040
10HT	4545	5360	6175	6875	7690	8390	9205	9905	10835	11650

Printed on 18/05/2024 18:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..