

AGRIMAX RT 765M - Spécifications techniques



Description

AGRIMAX RT 765M, un pneu de la série 70 de BKT, est idéal pour équiper les tracteurs les plus modernes utilisés dans les applications lourdes, telles que traitements de terrains, déplacements aux champs et sur route, vendange et pulvérisations. La large zone de contact garantit une traction et un confort optimaux sur toutes les surfaces et à tout moment. Le pneu se distingue de par ses excellentes qualités d'autonettoyage et le compactage du sol réduit. Deux tailles sont disponibles avec la technologie de ceintures en acier.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Pulvérisateur • Tracteur • Machine à vendanger

Version	SPECIAL
Type	TL
Tyre Size	710/70 R 38
LI/SS	166 D

Dimensions International Standard

Section Width (mm)	716
Overall Diameter (mm)	1959
Static Loaded Radius (mm)	859
Rolling Circumference (mm)	5751
SRI (mm)	925
Rim Rec	DW 23 B
ECE	E11-106R-005837
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
65	2915	3395	3870	4350	4825	5300
50	3065	3565	4065	4565	5065	5565
40	3195	3720	4240	4765	5285	5805
30	3355	3905	4450	5000	5550	6095
10 LT	3910	4550	5190	5830	6470	7105
10 HT	3355	3905	4450	5000	5550	6095

Printed on 18/05/2024 19:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..