

AT 621 - Spécifications techniques



Description

AT 621 convient pour les chargeuses-pelleteuses et les chargeuses compactes dans toutes les opérations d'excavation et de chargement dans le milieu agricole. La bande de roulement du pneu AT 621 est extra profonde afin d'assurer une résistance exceptionnelle aux coupures et déchirures et une durabilité plus élevée. En plus, ce pneu BKT est disponible en différentes versions pour répondre aux exigences les plus diverses des utilisateurs.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Chargeuse compacte • Chargeuse-pelleteuse
Industriel: Chargeuse-pelleteuse • Chargeur

| | |
|-----------|--------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 17.5/65 - 20 |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94028559 |
| Ply Rating | 10 |
| Section Width (inch) | 17.7 |
| Overall Diameter (inch) | 42.9 |
| Static Loaded Radius (inch) | 19.3 |
| Rolling Circumference (inch) | 129.7 |
| Rim Rec | W 14 L |
| ECE | E11-106R-005262 |
| TRA Code | R4 |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 36 |
| 5 | 7040 |

Printed on 18/05/2024 23:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..