

MULTIMAX MP 527 - Spécifications techniques



Description

MULTIMAX MP 527 est un pneu radial polyvalent pour chargeurs télescopiques et chargeuses compactes dans les applications agro-industrielles. Ce pneu présente un dessin à blocs de la bande de roulement qui garantit une excellente traction même sur les surfaces dures. Le flanc robuste du pneu assure une stabilité exceptionnelle en mode levage. MULTIMAX MP 527 est réalisé avec un mélange particulièrement résistant aux coupures et déchirures, ce qui se traduit par une longue vie du pneu.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Chargeuse compacte • Chargeuse télescopique

Industriel: Chargeuse compacte • Chargeuse télescopique

Version	STANDARD
Type	TL
Tyre Size	440/80 R 28 IND
LI/SS	156 A8/B

Dimensions International Standard

Section Width (mm)	441
Overall Diameter (mm)	1415
Static Loaded Radius (mm)	648
Rolling Circumference (mm)	4270
SRI (mm)	675
Rim Rec	DW 14 L
Rim Alt	DW 13 ; DW 13 L ; DW 15 L
ECE	E11-106R-002984

Load capacity (Kg)

km/h / bar	1.6	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6
50	2300	2725	2940	3150	3360	3575	3790	4000	-	-
40	2300	2725	2940	3150	3360	3575	3790	4000	-	-
30	2480	2930	3155	3380	3605	3830	4055	4280	-	-
25	2570	3040	3270	3505	3740	3970	4205	4440	-	-
10 Cyc.	2840	3470	3790	4105	4420	4735	5050	5370	5685	6000
Static	4360	5330	5810	6295	6780	7265	7750	8230	8715	9200

Printed on 19/05/2024 05:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..