

## RIDEMAX FL 693 M - Spécifications techniques



### Description

RIDEMAX FL 693 M est le pneu idéal pour les applications de transports fréquents sur route avec des remorques/camions-citernes. Conçu pour l'utilisation 75% sur route, RIDEMAX FL 693 M présente des prestations excellentes sur route et priorise aussi le confort et les propriétés d'auto-nettoyage. L'indice de vitesse classe D/E de la gamme est synonyme de vitesse élevée sur la route avec un gain de temps considérable. La résistance au roulement réduite contribue à l'économie de carburant, tandis que la tringle renforcée et les ceintures en acier assurent une durabilité avancée.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Véhicule citerne • Remorque

Version	STANDARD
Type	TL
Tyre Size	600/60 R 30.5
LI/SS	173 D

## Dimensions International Standard

Section Width (mm)	605
Overall Diameter (mm)	1495
Static Loaded Radius (mm)	681
Rolling Circumference (mm)	4495
SRI (mm)	725
Rim Rec	AG 20.00
Rim Alt	AG 18.00
ECE	E11-106R-007198

## Load capacity (Kg)

km/h / bar	1.0	1.2	1.6	2	2.4	2.8	3.2	3.6	4	4.5	5
70	2045	2250	2725	3020	3490	3965	4380	4795	5265	5620	5915
65	2245	2470	2990	3315	3835	4355	4810	5265	5785	6175	6500
50	2715	2990	3620	4015	4645	5270	5825	6375	7000	7475	7865
40	3050	3360	4070	4510	5220	5925	6545	7165	7870	8400	8840
30	3390	3730	4515	5010	5795	6580	7265	7955	8740	9325	9815
25	3545	3905	4725	5240	6060	6885	7600	8320	9145	9760	10270
10	4040	4450	5385	5970	6905	7840	8660	9480	10415	11115	11700

Printed on 19/05/2024 01:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..