

TR 463 - Spécifications techniques



Description

TR 463 a été particulièrement conçu pour les chargeuses pelleuses et les tracteurs industriels. Réalisé avec un mélange supérieur de la bande de roulement et avec une robuste carcasse en nylon, ce pneu garantit les meilleurs résultats dans les applications industrielles et OTR ainsi que sur les chantiers. TR 463 assure une excellente traction pour les roues motrices.

UM

US Standard

Construction

 BIAS

Machinery

Industriel: Chargeuse-pelleuse • Tracteur

Version	INDUSTRIAL
Type	TL
Tyre Size	18.4 - 26
LI/SS	156 A8

Dimensions US Standard

Usa code	94057221
Ply Rating	12
Section Width (inch)	18.9
Overall Diameter (inch)	56.1
Static Loaded Radius (inch)	25.1
Rolling Circumference (inch)	165.9
Rim Rec	DW 16 L
Rim Alt	DW 15 L
TRA Code	R4

Load capacity (lbs)

mph / psi	36
25	8820

Printed on 22/05/2024 20:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..