



FL 695 - Data Sheet



Description

FL 695 has been specifically designed for trailers in construction and transport applications with a unique center block tread pattern. Thanks to its strong casing, FL 695 can carry heavy loads maintaining stability in all conditions and its deep tread ensures optimal self-cleaning during on and off-road applications. Multiple steel cord layers reinforce this pattern against punctures.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Trailer

Industrial: Trailer

SIZE	Version	USACode	LI/SS	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
600/55 R 26.5	STEEL BELTED	94072897	173 D			AG20.00		23.3	52.6	24.4	161	TL	E11-106R-007937
650/55 R 26.5	STEEL BELTED	94067886	178 D			AG20.00	AG22.00	24.8	54.7	24.8	167	TL	E11-106R-007052
600/60 R 30.5	STEEL BELTED	94073832	179 D	179 D	179 D	AG20.00		24.1	58.9	27.3	180.6	TL	E11-106R-008503
710/50 R 30.5	STEEL BELTED	94074082	177 D	177 D	177 D	AG24.00	AG20.00	27.6	58.7	27.2	179.3	TL	E11-106R-008661

Printed on 18/05/2024 20:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..