

# MULTIMAX MP 522 - Technical Specifications



## Description

MULTIMAX MP 522 is the BKT multi-purpose tire developed for agro-industrial applications. It is suitable for all lifting and loading operations on vehicles such as telehandlers and compact loaders. Stability and traction are its strengths as well as outstanding puncture resistance. Thanks to its special compound, MULTIMAX MP 522 has an incredible cut and chip resistance.

## UM

International Standard

## Construction

 RADIAL

## Machinery

Agriculture: Compact Loader • Telehandler  
Industrial: Compact Loader • Telehandler

Version	STANDARD
Type	TL
Tyre Size	400/80 R 24 IND (16.0/80 R 24)
LI/SS	162 A8/B

## Dimensions International Standard

Section Width (mm)	404
Overall Diameter (mm)	1250
Static Loaded Radius (mm)	553
Rolling Circumference (mm)	3778
SRI (mm)	600
Rim Rec	DW 13
Rim Alt	DW 12 ; DW 13 L ; DW 14 L
ECE	E11-106R-002965

## Load capacity (Kg)

km/h / bar	1.6	2.0	2.4	2.8	3.2	3.4	3.6	4.0	4.4	4.6	4.8	5.0	5.2	5.4
50	1855	2185	2565	2900	3230	3350	3520	3895	4220	4435	4540	4750	-	-
40	1855	2185	2565	2900	3230	3350	3520	3895	4220	4435	4540	4750	-	-
30	1985	2340	2750	3105	3460	3590	3770	4170	4515	4745	4860	5085	-	-
25	2060	2430	2850	3220	3590	3725	3910	4330	4690	4925	5040	5275	-	-
10 Cyc.	2280	2785	3280	3850	4350	4600	4845	5280	5845	6090	6330	6655	6810	7125
Static	3500	4270	5030	5900	6670	7050	7430	8100	8960	9340	9710	10205	10445	10925

Printed on 18/05/2024 22:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..