

MULTIMAX MP 522 - Technical Specifications



Description

MULTIMAX MP 522 is the BKT multi-purpose tire developed for agro-industrial applications. It is suitable for all lifting and loading operations on vehicles such as telehandlers and compact loaders. Stability and traction are its strengths as well as outstanding puncture resistance. Thanks to its special compound, MULTIMAX MP 522 has an incredible cut and chip resistance.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Compact Loader • Telehandler

Industrial: Compact Loader • Telehandler

Version	STANDARD
Type	TL
Tyre Size	440/80 R 24 IND
LI/SS	161 A8/B

Dimensions US Standard

Usa code	94052257
Section Width (inch)	17.4
Overall Diameter (inch)	51.7
Static Loaded Radius (inch)	23.1
Rolling Circumference (inch)	155.8
Rim Rec	DW 14 L
Rim Alt	DW 13 ; DW 13 L ; DW 15 L
ECE	E11-106R-002966

Load capacity (lbs)

mph / psi	23	29	35	41	46	51	58	61	64
30	4890	5820	6640	7550	8470	9080	10200	-	-
25	4890	5820	6640	7550	8470	9080	10200	-	-
20	5250	6230	7100	8080	9060	9720	10910	-	-
15	5430	6460	7360	8380	9400	10090	11320	-	-
5 Cyc.	5970	7350	8650	9950	11330	12320	13930	14690	15300
Static	9150	11260	13260	15260	17360	18890	21350	22520	23460

Printed on 18/05/2024 17:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..