

RIDEMAX FL 693 M - Technical Specifications



Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tanker • Trailer

Version	STANDARD
Type	TL
Tyre Size	750/60 R 30.5
LI/SS	181 D

Dimensions US Standard

Usa code	94033812
Section Width (inch)	29.7
Overall Diameter (inch)	65.9
Static Loaded Radius (inch)	28.7
Rolling Circumference (inch)	200.5
Rim Rec	AG 24.00
ECE	E4-106R-001499

Load capacity (lbs)

mph / psi	15	17	23	29	35	41	46	52	58
45	6130	6960	8450	9780	11260	12750	13750	15230	16560
40	6730	7640	9280	10740	12370	14010	15100	16730	18190
30	8160	9250	11230	13000	14970	16950	18280	20260	22010
25	9160	10390	12620	14590	16820	19050	20530	22760	24730
15	10640	12070	14660	16960	19540	22130	23850	26440	28740
5	12120	13760	16700	19320	22270	25210	27180	30120	32740

Printed on 19/05/2024 00:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..