

RIDEMAX IT 697 (M+S) - Technical Specifications



Description

RIDEMAX IT 697 M+S represents the best response to the needs of modern farming contractors during winter operations. It is perfect for haulage and municipality applications. This winter tire for tractors ensures extraordinary grip for all operations on icy and snowy roads without the need of snow chains being mounted. Thanks to the tread grooves and the strong casing, a tractor can be driven in full stability, also at high speed levels. The tread design has been specially developed for heavy-duty services and ensures a low rolling resistance that provides fuel economy plus great stability.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	540/70R24 IND
LI/SS	170D/175A8

Dimensions International Standard

Section Width (mm)	535
Overall Diameter (mm)	1370
Static Loaded Radius (mm)	625
Rolling Circumference (mm)	4181
SRI (mm)	650
Rim Rec	DW 16 L
Rim Alt	DW18 L
ECE	E11-106R-007933

Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.5	5.0
65	2040	2520	2760	3240	3660	4080	4500	4920	5460	6000
50	2205	2725	2985	3500	3955	4410	4860	5315	5900	6480
40	2350	2900	3175	3730	4210	4695	5175	5660	6280	6900
30	2450	3025	3315	3890	4395	4900	5400	5905	6555	7200

Printed on 18/05/2024 17:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..