

RT 747 AGRO INDUSTRIAL - Technical Specifications



Description

RT 747 AGRO INDUSTRIAL is a radial agro-industrial tire suitable for compact loaders and telehandlers. Its extra wide lugs provide excellent traction and great stability in lifting operations. It has been designed with a special cut-and-chip resistance compound that enables the tire to carry heavy loads. RT 747 AGRO INDUSTRIAL is the right answer to all general farming operations that need outstanding versatility.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Compact Loader • Telehandler
 Industrial: Compact Loader • Telehandler

| | |
|-----------|-----------------------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 460/70 R 24 (17.5L R 24) |
| LI/SS | 159A8/156B |

Dimensions International Standard

| | |
|----------------------------|-------------------|
| Section Width (mm) | 465 |
| Overall Diameter (mm) | 1254 |
| Static Loaded Radius (mm) | 556 |
| Rolling Circumference (mm) | 3840 |
| SRI (mm) | 575 |
| Rim Rec | DW 15 L |
| Rim Alt | DW 14 L ; DW 16 L |
| ECE | E11-106R-005105 |

Load capacity (Kg)

| km/h / bar | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.5 | 4.0 |
|------------|------|------|------|------|------|------|------|-------|
| 50 | 1535 | 1890 | 2245 | 2560 | 2915 | 3265 | 3505 | 4000 |
| 40 | 1705 | 2100 | 2495 | 2845 | 3240 | 3630 | 3895 | 4375 |
| 30 | 1775 | 2185 | 2595 | 2960 | 3370 | 3775 | 4050 | 4550 |
| 25 | 1805 | 2225 | 2645 | 3015 | 3435 | 3850 | 4130 | 4640 |
| 10 Cyc | 2560 | 3150 | 3745 | 4270 | 4860 | 5445 | 5845 | 6565 |
| Static | 3920 | 4830 | 5740 | 6545 | 7450 | 8350 | 8960 | 10065 |

Printed on 18/05/2024 22:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..