

## AT 621 - Specifiche tecniche



### Description

AT 621 è idoneo per terne e pale compatte in tutte le operazioni di scavo e carico in ambito agricolo. Il battistrada dell'AT 621 è extra profondo per assicurare eccezionale resistenza a tagli e lacerazioni nonché maggiore durabilità. Inoltre, questo pneumatico BKT assicura ottime proprietà di autopulitura. AT 621 è disponibile in svariate versioni per rispondere alle esigenze più diverse degli utilizzatori.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Pala compatta • Terna

Industriale: Terna • Pala caricatrice

Version	STANDARD
Type	TL
Tyre Size	400/70 - 20
LI/SS	152 B/168 A2

## Dimensions International Standard

Ply Rating	16
Section Width (mm)	405
Overall Diameter (mm)	1090
Static Loaded Radius (mm)	494
Rolling Circumference (mm)	3271
Rim Rec	13
Rim Alt	12 SDC ; 13 SDC ; 14
TRA Code	R4

## Load capacity (Kg)

km/h / bar	4.00	5.00
50	3550	-
10	-	5600

Printed on 18/05/2024 17:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..