

AT 621 - Scheda tecnica



Description

AT 621 è idoneo per terne e pale compatte in tutte le operazioni di scavo e carico in ambito agricolo. Il battistrada dell'AT 621 è extra profondo per assicurare eccezionale resistenza a tagli e lacerazioni nonché maggiore durabilità. Inoltre, questo pneumatico BKT assicura ottime proprietà di autopulitura. AT 621 è disponibile in svariate versioni per rispondere alle esigenze più diverse degli utilizzatori.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Pala compatta • Terna

Industriale: Terna • Pala caricatrice

| SIZE | Version | TRA Code | LI/SS | LI/SS DRIVE WHEEL | LI/SS FREE ROLLING | PR | RIM REC | RIM ALT | SW | OD | SLR | RC | Type | ECE |
|----------------------------|---------------|----------|--------------|-------------------|--------------------|----|--------------|----------------------|-----|------|-----|------|------|-----------------|
| 33 X 12.5 - 15 | STANDARD | R4 | | | | 8 | 10.00 F SDC | | 318 | 851 | 394 | 2507 | TT | E11-106R-005230 |
| 10.0/75 - 15.3 | STANDARD | | 127 A6 | | | 10 | 9.0 | | 267 | 780 | 373 | 2385 | TL | E11-106R-007466 |
| 12.5/70 - 16 | STANDARD | R4 | | | | 14 | 10 LB | | 315 | 855 | 385 | 2584 | TL | |
| 12.5/70 - 16 | STANDARD | R4 | | | | 14 | 10 LB | | 315 | 855 | 385 | 2584 | TT | |
| 12.5/70 - 16 | STANDARD | R4 | | | | 8 | 10 LB | | 315 | 855 | 385 | 2584 | TL | E11-106R-005295 |
| 9.00 - 16 | INDUSTRIAL | | 137 A6 | | | 16 | 6.50 H | 6.00 G | 260 | 925 | 0 | 0 | TT | E11-106R-005364 |
| 12.5/80 - 18 | INDUSTRIAL HD | R4 | | 135 A8 | 148 A8 | 16 | W 9 | 11.0 | 308 | 987 | 434 | 2916 | TL | E11-106R-005365 |
| 12.5/80 - 18 | SPECIAL | R4 | | 129 A8 | 142 A8 | 12 | W 9 | 11.0 | 308 | 987 | 434 | 2916 | TL | E11-106R-005329 |
| 12.5/80 - 18 | STANDARD | R4 | | 129 A8 | 142 A8 | 12 | W 9 | 11.0 | 308 | 987 | 434 | 2916 | TL | E11-106R-003388 |
| 12.5/80 - 18 | STANDARD | R4 | | 135 A8 | 148 A8 | 16 | W 9 | 11.0 | 308 | 987 | 434 | 2916 | TT | E11-106R-006957 |
| 12.5/80 - 18 | STANDARD | R4 | | 135 A8 | 148 A8 | 16 | W 9 | 11.0 | 308 | 987 | 434 | 2916 | TL | E11-106R-006957 |
| 12.5/80 - 18 | STANDARD | R4 | | 129 A8 | 142 A8 | 12 | W 9 | 11.0 | 308 | 987 | 434 | 2916 | TT | E11-106R-003388 |
| 15.5/60 - 18 | STANDARD | R4 | 139 A2 | | | 10 | W 13 | | 394 | 940 | 428 | 2871 | TL | E11-106R-003575 |
| 15.5/60 - 18 | STANDARD | R4 | 141 A2 | | | 12 | W 13 | | 394 | 940 | 428 | 2871 | TL | E11-106R-004651 |
| 15.5/70 - 18 (400/70 - 18) | STANDARD | R4 | | | | 10 | W 13 | | 400 | 1030 | 474 | 3111 | TL | E11-106R-005260 |
| 385/65 D 19.5 | STANDARD | | 165 A2 | | | 16 | 11.75 | 12.25 | 390 | 1020 | 478 | 3136 | TL | E11-106R-006419 |
| 12.5 - 20 | STANDARD | R4 | | | | 12 | 11.0 | | 325 | 1040 | 0 | 0 | TT | E11-106R-005293 |
| 17.5/65 - 20 | STANDARD | R4 | | | | 10 | W 14 L | | 450 | 1090 | 490 | 3294 | TL | E11-106R-005262 |
| 400/70 - 20 | STANDARD | R4 | 152 B/168 A2 | | | 16 | 13 | 12 SDC ; 13 SDC ; 14 | 405 | 1090 | 494 | 3271 | TL | |
| 400/70 - 20 | STANDARD | R4 | 149 A8 | | | | 13 | 12 SDC ; 13 SDC ; 14 | 405 | 1090 | 494 | 3271 | TL | E11-106R-005289 |
| 42 X 17 - 20 | STANDARD | R4 | | | | 10 | 14.00 TG SDC | | 432 | 1073 | 480 | 3198 | TT | E11-106R-005294 |
| 16.9 - 24 | INDUSTRIAL | R4 | 149 A8 | | | 12 | DW 15 L | DW 14 L | 450 | 1302 | 590 | 3906 | TL | E11-106R-005374 |
| 17.5L - 24 | STANDARD | R4 | 139 A8 | | | 8 | DW 15 L | DW 14 L | 450 | 1255 | 558 | 3752 | TL | E11-106R-005267 |

| | | | | | | | | | | | | |
|-------------------|------------|----|--------|----|---------|---------|-----|------|-----|------|----|-----------------|
| 19.5L - 24 | STANDARD | R4 | 151 A8 | 12 | DW 16 L | | 482 | 1305 | 587 | 3936 | TL | E11-106R-005373 |
| 18.4 - 26 | STANDARD | R4 | 156 A8 | 12 | DW 16 L | DW 15 L | 480 | 1425 | 649 | 4288 | TL | E11-106R-003634 |
| 16.9 - 28 | INDUSTRIAL | R4 | 154 A8 | 14 | DW 15 L | DW 14 L | 450 | 1410 | 639 | 4199 | TL | E11-106R-007209 |
| 16.9 - 28 | INDUSTRIAL | R4 | 152 A8 | 12 | DW 15 L | DW 14 L | 450 | 1410 | 639 | 4199 | TT | E11-106R-003635 |
| 16.9 - 28 | INDUSTRIAL | R4 | 152 A8 | 12 | DW 15 L | DW 14 L | 450 | 1410 | 639 | 4199 | TL | E11-106R-003635 |
| 16.9 - 30 | INDUSTRIAL | R4 | 153 A8 | 12 | DW 15 L | DW 14 L | 450 | 1460 | 670 | 4398 | TL | E11-106R-005375 |

Printed on 18/05/2024 22:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..