

## EARTHMAX SR 31 - Specifiche tecniche



### Description

EARTHMAX SR 31 è uno pneumatico radiale All Steel progettato per dumper rigidi e pale gommate. Le cinture in acciaio multistrato assicurano forza e stabilità straordinarie, mentre il disegno non-direzionale rigido a blocchi garantisce trazione e manovrabilità eccellenti, anche su fondo fangoso. Oltre allo straordinario comfort di guida, EARTHMAX SR 31 si distingue anche per una miscela speciale del battistrada, particolarmente resistente ai tagli e al calore. La struttura radiale della carcassa offre inoltre una bassa resistenza al rotolamento con conseguenti risparmi significativi di carburante.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Industriale: Dozer • Pala caricatrice

OTR: Dumper articolato • Dozer • Pala caricatrice

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	26.5 R 25
LI/SS	193 B/202 A2

## Dimensions International Standard

TKPH	230
Overall Width (mm)	689
Overall Diameter (mm)	1742
Static Loaded Radius (mm)	766
Rolling Circumference (mm)	5200
Rim Rec	22.00/3.0
Star Rating	**/*
TRA Code	E3/L3

## Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00	5.25
50	9500	9750	10300	10600	11200	11500
10	12850	13200	14000	14500	15000	--

Printed on 18/05/2024 17:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..