

EARTHMAX SR 31 - Specifiche tecniche



Description

EARTHMAX SR 31 è uno pneumatico radiale All Steel progettato per dumper rigidi e pale gommate. Le cinture in acciaio multistrato assicurano forza e stabilità straordinarie, mentre il disegno non-direzionale rigido a blocchi garantisce trazione e manovrabilità eccellenti, anche su fondo fangoso. Oltre allo straordinario comfort di guida, EARTHMAX SR 31 si distingue anche per una miscela speciale del battistrada, particolarmente resistente ai tagli e al calore. La struttura radiale della carcassa offre inoltre una bassa resistenza al rotolamento con conseguenti risparmi significativi di carburante.

UM

US Standard

Construction

 RADIAL

Machinery

Industriale: Dozer • Pala caricatrice

OTR: Dumper articolato • Dozer • Pala caricatrice

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	26.5 R 25
LI/SS	209 A2

Dimensions US Standard

Usa code	94054381
Overall Width (inch)	27.1
Overall Diameter (inch)	68.6
Static Loaded Radius (inch)	30.2
Rolling Circumference (inch)	204.7
Rim Rec	22.00/3.0
Star Rating	**
TRA Code	L3

Load capacity (lbs)

mph / psi	76	80	83	87	91	94
5	34200	35300	36400	37500	39700	40800

Printed on 18/05/2024 18:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..