

EARTHMAX SR 41 - Specifiche tecniche



Description

EARTHMAX SR 41 è uno pneumatico radiale All Steel ideale per loader and dozer nelle applicazioni di trasporto, carico e livellamento. Grazie alla sua struttura in acciaio e al particolare disegno a blocchi, EARTHMAX SR 41 offre un'eccellente resistenza alle forature e una durabilità prolungata. Oltre a molte ore operative senza tempi di fermo macchina, lo pneumatico assicura un comfort eccezionale. EARTHMAX SR 41 (E-4/L-4) è uno pneumatico All Steel ideale per dumper articolati, loader e dozer.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Dumper articolato • Dozer • Pala caricatrice • Dumper di basso profilo

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	29.5 R 25
LI/SS	200 B

Dimensions International Standard

TKPH	225
Overall Width (mm)	761
Overall Diameter (mm)	1861
Static Loaded Radius (mm)	830
Rolling Circumference (mm)	5510
Rim Rec	25.00/3.5
Star Rating	**
TRA Code	E4

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00	5.25
50	11500	11800	12500	12850	13600	14000

Printed on 18/05/2024 22:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..