

EARTHMAX SR 468 - Specifiche tecniche



Description

EARTHMAX SR 468 è uno pneumatico radiale All Steel specificamente progettato per camion rigidi da trasporto. Il design unico del battistrada con mescole speciali lo rende perfetto per operazioni di scavo su terreni duri, rocciosi e complessi. I blocchi del battistrada con intagli sulla circonferenza e design a intreccio assicurano un'efficace dissipazione del calore. Inoltre, la robusta spalla quadrata aiuta ad espellere i singoli sassi per proteggere lo pneumatico da danneggiamenti. EARTHMAX SR 468 è il frutto della più avanzata tecnologia BKT, sviluppata per trasportare carichi pesanti, garantire una maggiore durata e offrire resistenza ai tagli e alle perforazioni da roccia.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Dumper rigido

Version	HEAT RESISTANT COMPOUND
Type	TL
Tyre Size	37.00 R 57
LI/SS	245 B

Dimensions US Standard

Usa code	94069347
TMPH	699
Overall Width (inch)	40.6
Overall Diameter (inch)	134.8
Static Loaded Radius (inch)	59.8
Rolling Circumference (inch)	406.1
Rim Rec	27.00/6.0
Rim Alt	29.00/6.0
Star Rating	**
TRA Code	E4

Load capacity (lbs)

mph / psi	80	83	87	91	94	98	102
30	96500	99000	102000	104500	107500	110000	113500

Printed on 18/05/2024 21:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..