

EARTHMAX SR 49 M - Specifiche tecniche



Description

EARTHMAX SR 49 M è uno pneumatico All Steel con un particolare disegno non direzionale sviluppato per pale LHD, dumper di basso profilo (LPDT), pale gommate e dozer. che operano in condizioni severe in ambienti rocciosi, principalmente nelle miniere sotterranee. EARTHMAX SR 49 M è ideale per operazioni dure che richiedono trazione e stabilità eccezionali. Il battistrada di profondità L-4 e la miscela con formula speciale UMS (underground mine service) assicurano una maggiore resistenza all'usura del battistrada nonché eccellente resistenza contro tagli di roccia e forature.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Dozer • Pala LHD • Pala caricatrice • Dumper di basso profilo

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	26.5 R 25
LI/SS	202 A2

Dimensions International Standard

Overall Width (mm)	708
Overall Diameter (mm)	1782
Static Loaded Radius (mm)	801
Rolling Circumference (mm)	5297
Rim Rec	22.00/3.0
Star Rating	*
TRA Code	L4

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00
10	12850	13200	14000	14500	15000

Printed on 19/05/2024 05:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..