

RIDEMAX FL 693 M - Specifiche tecniche



Description

RIDEMAX FL 693 M è lo pneumatico ideale per chi deve percorrere frequentemente tratti stradali con rimorchi/autobotti. Sviluppato per un utilizzo del 75% su strada, RIDEMAX FL 693 M mostra delle prestazioni eccellenti su strada, dando la priorità al comfort e alle proprietà di autopulitura. L'indice di velocità classe D/E della gamma è sinonimo di velocità più elevate sui percorsi stradali con significativo risparmio di tempo. La bassa resistenza al rotolamento contribuisce ad un consumo minore di carburante, mentre il tallone rinforzato e le cinture in acciaio garantiscono una durabilità superiore.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Autobotte • Rimorchio

Version	STANDARD
Type	TL
Tyre Size	500/60 R 22.5
LI/SS	155 D/152 E

Dimensions International Standard

Section Width (mm)	503
Overall Diameter (mm)	1172
Static Loaded Radius (mm)	531
Rolling Circumference (mm)	3577
SRI (mm)	550
Rim Rec	AG 16.00
Rim Alt	15.00 ; 17.00
ECE	E4-106R-001402

Load capacity (Kg)

km/h / bar	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1320	1495	1775	2095	2400	2665	2985	3270	3550
65	1435	1630	1940	2290	2620	2910	3255	3565	3875
50	1740	1970	2345	2770	3170	3520	3940	4315	4690
40	1955	2215	2635	3110	3560	3955	4430	4850	5270
25	2270	2575	3065	3615	4135	4595	5145	5635	6125
10	2585	2930	3490	4120	4710	5235	5860	6420	6975

Printed on 19/05/2024 00:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..