

RIDEMAX FL 693 M - Specifiche tecniche



Description

RIDEMAX FL 693 M è lo pneumatico ideale per chi deve percorrere frequentemente tratti stradali con rimorchi/autobotti. Sviluppato per un utilizzo del 75% su strada, RIDEMAX FL 693 M mostra delle prestazioni eccellenti su strada, dando la priorità al comfort e alle proprietà di autopulitura. L'indice di velocità classe D/E della gamma è sinonimo di velocità più elevate sui percorsi stradali con significativo risparmio di tempo. La bassa resistenza al rotolamento contribuisce ad un consumo minore di carburante, mentre il tallone rinforzato e le cinture in acciaio garantiscono una durabilità superiore.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Autobotte • Rimorchio

| | |
|-----------|---------------|
| Version | HD |
| Type | TL |
| Tyre Size | 710/50 R 26.5 |
| LI/SS | 179 D |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Section Width (mm) | 727 |
| Overall Diameter (mm) | 1383 |
| Static Loaded Radius (mm) | 606 |
| Rolling Circumference (mm) | 4217 |
| SRI (mm) | 650 |
| Rim Rec | AG 24.00 |
| Rim Alt | AG 20.00 |
| ECE | E11-106R-006008 |

Load capacity (Kg)

| km/h / bar | 1.0 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 | 5.0 | 6.0 |
|------------|------|------|------|------|------|------|------|------|-------|-------|-------|
| 70 | 1765 | 2260 | 2825 | 3175 | 3670 | 4165 | 4590 | 5010 | 5505 | 6210 | 7055 |
| 65 | 1940 | 2480 | 3100 | 3490 | 4030 | 4575 | 5040 | 5505 | 6045 | 6820 | 7750 |
| 50 | 2345 | 3005 | 3755 | 4225 | 4880 | 5535 | 6100 | 6660 | 7320 | 8255 | 9380 |
| 40 | 2635 | 3375 | 4220 | 4745 | 5485 | 6220 | 6855 | 7485 | 8225 | 9280 | 10540 |
| 30 | 2930 | 3750 | 4685 | 5270 | 6090 | 6910 | 7610 | 8315 | 9130 | 10305 | 11705 |
| 25 | 3065 | 3920 | 4900 | 5515 | 6370 | 7225 | 7960 | 8695 | 9555 | 10780 | 12245 |
| 10 | 3490 | 4465 | 5580 | 6280 | 7255 | 8235 | 9070 | 9905 | 10885 | 12280 | 13950 |

Printed on 18/05/2024 20:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..