

## RIDEMAX FL 693 M - Specifiche tecniche



### Description

RIDEMAX FL 693 M è lo pneumatico ideale per chi deve percorrere frequentemente tratti stradali con rimorchi/autobotti. Sviluppato per un utilizzo del 75% su strada, RIDEMAX FL 693 M mostra delle prestazioni eccellenti su strada, dando la priorità al comfort e alle proprietà di autopulitura. L'indice di velocità classe D/E della gamma è sinonimo di velocità più elevate sui percorsi stradali con significativo risparmio di tempo. La bassa resistenza al rotolamento contribuisce ad un consumo minore di carburante, mentre il tallone rinforzato e le cinture in acciaio garantiscono una durabilità superiore.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricoltura: Autobotte • Rimorchio

Version	STANDARD
Type	TL
Tyre Size	850/50 R 30.5
LI/SS	182 D

## Dimensions US Standard

Usa code	94034505
Section Width (inch)	33.9
Overall Diameter (inch)	64
Static Loaded Radius (inch)	28.3
Rolling Circumference (inch)	193.9
Rim Rec	AG 28.00
ECE	E4-106R-001500

## Load capacity (lbs)

mph / psi	15	17	23	29	35	41	46	52	58
45	6320	7160	8700	10060	11600	13140	14160	15700	17050
40	6930	7870	9560	11060	12740	14430	15550	17240	18740
30	8400	9520	11570	13380	15420	17460	18830	20870	22670
25	9440	10710	13010	15050	17340	19630	21150	23460	25480
15	10970	12440	15100	17470	20140	22810	24580	27250	29610
5	12490	14170	17210	19910	22940	25980	28000	31040	33730

Printed on 18/05/2024 18:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..