

## XL GRIP (L3) - Specifiche tecniche



### Description

XL GRIP (E-3/L-3) è uno pneumatico a tele incrociate di base larga (wide) sviluppato per loader al fine di minimizzare il rischio di tagli e perforazioni nelle applicazioni pesanti di carico. Lo pneumatico assicura eccellente trazione insieme ad un ciclo di vita prolungato del prodotto.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industriale: Pala caricatrice

OTR: Dozer • Pala caricatrice

Version	STANDARD
Type	TL
Tyre Size	16.0/70 - 20

## Dimensions US Standard

Usa code	94030538
Ply Rating	16
Overall Width (inch)	15.9
Overall Diameter (inch)	42.9
Static Loaded Radius (inch)	18.9
Rolling Circumference (inch)	129.7
Rim Rec	13 SDC
TRA Code	L3

## Load capacity (lbs)

mph / psi	58	75
30	7750	-
5	-	12640

Printed on 18/05/2024 22:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..