

## AGRIMAX FORCE - Especificações técnicas



### Description

AGRIMAX FORCE, o produto de ponta da BKT, é um pneu radial devidamente projetado para aplicações de tratamento do terreno, de transporte e de colheita com tratores de elevada potência, garantindo máximas prestações e eficiência. Com a tecnologia IF, este pneu permite-lhe transportar cargas pesadas a pressões de enchimento inferiores em comparação com o pneu estandarte reduzindo a compactação do solo. AGRIMAX FORCE é dotado de talão reforçado e assegura uma tração maior, propriedades de autolimpeza e economia de combustível, bem como uma experiência de condução confortável.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricultura: Ceifeira • Trator de alta potencia

Version	STANDARD
Type	TL
Tyre Size	IF 750/75 R 46 CFO
LI/SS	186 D

## Dimensions International Standard

Section Width (mm)	742
Overall Diameter (mm)	2294
Static Loaded Radius (mm)	1032
Rolling Circumference (mm)	6802
SRI (mm)	1075
Rim Rec	DW 25 B
ECE	E11-106R-006491
TRA Code	R1W

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	4060	4665	5355	6050	6740	7430	8125	8645
From 65 to 40	4465	5130	5890	6650	7410	8170	8930	9500
30	4640	5335	6125	6915	7705	8495	9285	9880
20	4820	5540	6360	7180	8000	8820	9640	10260
10	5670	6515	7480	8445	9410	10370	11340	12065
Upto 30 Cyc	5800	6665	7655	8645	9630	10620	11605	12350
Upto 15 Cyc	6920	7950	9125	10305	11485	12660	13840	14725
Upto 10 Cyc	7590	8720	10010	11305	12595	13885	15180	16150
10HT	4640	5335	6125	6915	7705	8495	9285	9880

Printed on 18/05/2024 18:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..