

AGRIMAX FORCE - Especificações técnicas



Description

AGRIMAX FORCE, o produto de ponta da BKT, é um pneu radial devidamente projetado para aplicações de tratamento do terreno, de transporte e de colheita com tratores de elevada potência, garantindo máximas prestações e eficiência. Com a tecnologia IF, este pneu permite-lhe transportar cargas pesadas a pressões de enchimento inferiores em comparação com o pneu estandarte reduzindo a compactação do solo. AGRIMAX FORCE é dotado de talão reforçado e assegura uma tração maior, propriedades de autolimpeza e economia de combustível, bem como uma experiência de condução confortável.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Ceifeira • Trator de alta potencia

| | |
|-----------|--------------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | IF 800/70 R 38 CFO |
| LI/SS | 184 D |

Dimensions US Standard

| | |
|------------------------------|---------------------------|
| Usa code | 94055784 |
| Section Width (inch) | 31.3 |
| Overall Diameter (inch) | 82.1 |
| Static Loaded Radius (inch) | 36.3 |
| Rolling Circumference (inch) | 243.5 |
| Rim Rec | DW 27 B |
| Rim Alt | DW 25 B, DW 28 B, DW 30 B |
| ECE | E11-106R-006497 |
| TRA Code | R1W |

Load capacity (lbs)

| mph / psi | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|---------------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 8480 | 9920 | 11360 | 12630 | 13900 | 14980 | 16790 | 18050 |
| from 40 to 25 | 9330 | 10910 | 12500 | 13890 | 15820 | 16470 | 18450 | 19800 |
| 20 | 9690 | 11340 | 13000 | 14440 | 15880 | 17120 | 19180 | 20630 |
| 12 | 10060 | 11780 | 13490 | 14990 | 16490 | 17780 | 19920 | 21430 |
| 5 | 11840 | 13860 | 15870 | 17640 | 19400 | 20910 | 23420 | 25200 |
| Upto 20 Cyc | 12110 | 14190 | 16250 | 18050 | 19850 | 21410 | 23980 | 25790 |
| Upto 10 Cyc | 14450 | 16910 | 19370 | 21530 | 23680 | 25520 | 28590 | 30750 |
| Upto 5 Cyc | 15850 | 18550 | 21240 | 23610 | 25970 | 27990 | 31360 | 33730 |
| 5 HT | 9690 | 11340 | 13000 | 14440 | 15880 | 17120 | 19180 | 20630 |

Printed on 18/05/2024 17:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..