

AGRIMAX RT 600 - Especificações técnicas

Description

AGRIMAX RT 600 é o pneu apropriado para prados e aplicações para a colheita e o espalhamento. Graças à sua ampla área de contacto, AGRIMAX RT 600 garante uma distribuição de pressão otimizada no terreno reduzindo os danos nos prados e protegendo o solo. Graças à tecnologia com ombros arredondados e um número elevado de blocos, assegura ótima estabilidade e tração.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Ceifeira • Espalhador • Trator



Version	STANDARD
Type	TL
Tyre Size	540/65 R 28
LI/SS	142 D/145 A8

Dimensions US Standard

Usa code	94053704
Section Width (inch)	20.9
Overall Diameter (inch)	55.6
Static Loaded Radius (inch)	25.3
Rolling Circumference (inch)	165.4
Rim Rec	W 16 L
Rim Alt	W 18 L
ECE	E11-106R-002980

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
40	3270	3860	4390	4920	5380	5840
30	3440	4060	4610	5160	5650	6140
25	3580	4220	4790	5380	5890	6390
20	3770	4440	5050	5650	6190	6720
5 LT	4400	5180	5890	6590	7220	7840
5 HT	3770	4440	5050	5650	6190	6720

Printed on 22/05/2024 23:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..