

AGRIMAX RT 600 - Especificações técnicas

Description

AGRIMAX RT 600 é o pneu apropriado para prados e aplicações para a colheita e o espalhamento. Graças à sua ampla área de contacto, AGRIMAX RT 600 garante uma distribuição de pressão otimizada no terreno reduzindo os danos nos prados e protegendo o solo. Graças à tecnologia com ombros arredondados e um número elevado de blocos, assegura ótima estabilidade e tração.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Ceifeira • Espalhador • Trator



Version	STANDARD
Type	TL
Tyre Size	650/75 R 32
LI/SS	172 A8/B

Dimensions International Standard

Section Width (mm)	655
Overall Diameter (mm)	1789
Static Loaded Radius (mm)	807
Rolling Circumference (mm)	5416
SRI (mm)	850
Rim Rec	DW 21 B
Rim Alt	DW 20 B ; DW 23 B
ECE	E11-106R-004755

Load capacity (Kg)

km/h / bar	0.8	1.0	1.4	1.6	2.0	2.4	2.8	3.2	3.4	3.8
50	2900	3340	4095	4475	4915	5355	5800	6300	-	-
40	2900	3340	4095	4475	4915	5355	5800	6300	-	-
30	3105	3575	4385	4790	5265	5735	6210	6745	-	-
10 LT	3885	4480	5490	6000	6590	7180	7770	8445	-	-
10 HT	3105	3575	4385	4790	5265	5735	6210	6745	-	-
10 Cyc.	-	4770	6105	6695	7765	8515	9320	10125	10285	10710

Printed on 22/05/2024 18:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..