

AGRIMAX RT 600 - Especificações técnicas

Description

AGRIMAX RT 600 é o pneu apropriado para prados e aplicações para a colheita e o espalhamento. Graças à sua ampla área de contacto, AGRIMAX RT 600 garante uma distribuição de pressão otimizada no terreno reduzindo os danos nos prados e protegendo o solo. Graças à tecnologia com ombros arredondados e um número elevado de blocos, assegura ótima estabilidade e tração.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Ceifeira • Espalhador • Trator



Version	STANDARD
Type	TL
Tyre Size	750/65 R 26
LI/SS	171 A8/B

Dimensions US Standard

Usa code	94064311
Section Width (inch)	29.5
Overall Diameter (inch)	64.4
Static Loaded Radius (inch)	29
Rolling Circumference (inch)	196.3
Rim Rec	DW 24 B
Rim Alt	DW 23 B ; DW 25 B
ECE	E11-106R-006182

Load capacity (lbs)

mph / psi	12	15	17	20	23	29	35	41	46	49	55
30	6240	7190	8130	8820	9630	10710	11530	12610	13560	-	-
25	6240	7190	8130	8820	9630	10710	11530	12610	13560	-	-
20	6680	7700	8720	9450	10320	11470	12350	13500	14520	-	-
5 LT	8370	9630	10910	11820	12910	14360	15450	16910	18180	-	-
5 HT	6680	7700	8720	9450	10320	11470	12350	13500	14520	-	-
5 Cyc	-	11550	13070	14160	15460	17220	18520	20260	21780	22130	23050

Printed on 22/05/2024 23:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..