

AT 621 - Especificações técnicas



Description

AT 621 é apropriado para retroescavadoras e pás compactas, em todas as operações de escavação e carga, em âmbito agrícola. O piso do pneu do AT 621 é extra profundo para assegurar uma resistência excepcional aos cortes e às lacerações, bem como uma maior durabilidade. Além disso, este pneu BKT fornece ótimas propriedades de autolimpagem. AT 621 está disponível em inúmeras versões para responder às exigências mais variadas dos utilizadores.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Carregadora compacta • Retroescavadora
Industrial: Retroescavadora • Carregadora

Version	STANDARD
Type	TT
Tyre Size	12.5/70 - 16

Dimensions US Standard

Usa code	94054350
Ply Rating	14
Section Width (inch)	12.4
Overall Diameter (inch)	33.7
Static Loaded Radius (inch)	15.2
Rolling Circumference (inch)	101.7
Rim Rec	10 LB
TRA Code	R4

Load capacity (lbs)

mph / psi	64
5	4940

Printed on 18/05/2024 22:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..