

## EARTHMAX SR 313 - Especificações técnicas



### Description

O EARTHMAX SR 313 é um pneu radial integralmente em aço, desenhado para os camiões basculantes articulados e pás carregadoras a trabalhar em terrenos rochosos duros. Com o composto resistente aos cortes e design de piso especial, protege contra os cortes e danos e oferece propriedades de autolimpeza. O design quadrado maximiza o contacto com o solo, garantindo excelente manobrabilidade. A construção radial integralmente em aço com lonas de cima de várias camadas proporciona durabilidade adicional. O EARTHMAX SR 313 é o pneu ideal para transporte, bem como carga e transporte.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Dumper Articulado • Carregadora

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	15.5 R 25
LI/SS	160 B/169 A2

## Dimensions International Standard

TKPH	135
Overall Width (mm)	394
Overall Diameter (mm)	1265
Static Loaded Radius (mm)	566
Rolling Circumference (mm)	3822
Rim Rec	12.00/1.3
Star Rating	**/*
TRA Code	E3/L3

## Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00	5.25
50	3650	3875	4000	4250	4375	4500
10	5000	5150	5450	5600	5800	-

Printed on 18/05/2024 21:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..