

EARTHMAX SR 31 - Especificações técnicas



Description

EARTHMAX SR 31 é um pneu All Steel radial especialmente projetado para dumper rígidos e carregadoras de rodas. Os cintos em aço multicamada asseguram força e estabilidade extraordinárias, enquanto o desenho não direcional rígido caracterizado por blocos garante tração e capacidade de manobra excelentes, mesmo em terreno com lama. Além do conforto na condução extraordinário, EARTHMAX SR 31 também se destaca por ter um composto de borracha especial do piso do pneu, especialmente resistente aos cortes e ao calor. A estrutura radial da carcaça proporciona ainda uma baixa resistência ao rolamento com consequentes poupanças significativas de combustível.

UM

International Standard

Construction

 RADIAL

Machinery

Industrial: Trator de esteira • Carregadora

OTR: Dumper Articulado • Trator de esteira • Carregadora

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	20.5 R 25
LI/SS	177 B/186 A2

Dimensions International Standard

TKPH	170
Overall Width (mm)	540
Overall Diameter (mm)	1480
Static Loaded Radius (mm)	663
Rolling Circumference (mm)	4449
Rim Rec	17.00/2.0
Rim Alt	--
Star Rating	**/*
TRA Code	E3/L3

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00	5.25
50	5800	6150	6500	6700	6900	7300
10	8000	8250	8750	9000	9500	-

Printed on 18/05/2024 17:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..