

EARTHMAX SR 41 - Dados técnicos



Description

EARTHMAX SR 41 é um pneu radial All Steel perfeito para carregadoras e tratores de esteira nas aplicações de transporte, carga e nivelamento. Graças à sua estrutura All Steel e ao desenho caracterizado por blocos, EARTHMAX SR 41 proporciona uma resistência excelente aos furos e uma durabilidade prolongada. Além das muitas horas de trabalho sem ter de parar a máquina, o pneu assegura um conforto excepcional. EARTHMAX SR 41 (E-4/L-4) é um pneu radial All Steel ideal para dumper articulados, pás carregadoras e escavadoras.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Dumper Articulado • Trator de esteira • Carregadora
• Dumper de baixo perfil

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
23.5 R 25	CUT RESISTANT COMPOUND	94053353	E4/L4	**/*	185 B/195 A2	19.50/2.5		24.2	63.4	28.5	188.6	TL	110
26.5 R 25	CUT RESISTANT COMPOUND	94041206	E4/L4	**/*	193 B/202 A2	22.00/3.0		26.7	68.6	30.5	202.8	TL	127
26.5 R 25	CUT RESISTANT COMPOUND (UMS)	94056583	E4	****		22.00/3.0		26.7	68.6	30.5	202.8	TL	0
26.5 R 25	STANDARD COMPOUND	94041527	E4	**	193 B	22.00/3.0		26.7	68.6	30.5	202.8	TL	161
29.5 R 25	CUT RESISTANT COMPOUND	94058013	E4	**	200 B	25.00/3.5		30	73.3	32.7	216.9	TL	154
29.5 R 25	CUT RESISTANT COMPOUND	94070367	L4	***	221 A2	25.00/3.5		30	73.3	32.7	216.9	TL	0
29.5 R 25	CUT RESISTANT COMPOUND	94039852	E4/L4	**/*	200 B/208 A2	25.00/3.5		30	73.3	32.7	216.9	TL	154
29.5 R 25	CUT RESISTANT COMPOUND (UMS)	94051052	E4	****		25.00/3.5		30	73.3	32.7	216.9	TL	0
29.5 R 25	STANDARD COMPOUND	94041169	E4	**	200 B	25.00/3.5		30	73.3	32.7	216.9	TL	195
875/65 R 29 (35/65 R 29)	CUT RESISTANT COMPOUND	94059911	E4/L4	**/*	203 B/214 A2	27.00/3.50	27.00/3.0, 28.00/3.5	34.6	73.4	33	223.6	TL	164
875/65 R 29 (35/65 R 29)	CUT RESISTANT COMPOUND	94059928	E4	**	203 B	27.00/3.50	27.00/3.0, 28.00/3.5	34.6	73.4	33	223.6	TL	164
875/65 R 29 (35/65 R 29)	CUT RESISTANT COMPOUND	94059935	L4	*	214 A2	27.00/3.50	27.00/3.0, 28.00/3.5	34.6	73.4	33	223.6	TL	0
875/65 R 29 (35/65 R 29)	CUT RESISTANT COMPOUND	94064359	L4	**	221 A2	27.00/3.5	27.00/3.0; 28.00/3.5	34.6	73.4	33	223.6	TL	0
35/65 R 33	CUT RESISTANT COMPOUND (UMS)	94069415	E4	****		28.00/3.5	--	35.3	81.2	36.5	247.4	TL	0

Printed on 18/05/2024 22:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..