

FL 630 ULTRA - Especificações técnicas



Description

FL 630 ULTRA é idóneo para aplicações com reboques, cisternas móveis e espalhadores. Gracias ao talão reforçado e o particular desenho do piso do pneu, o pneu é ideal para um uso polivalente em qualquer tipo de terreno o na estrada. FL 630 ULTRA é sinónimo de uma compactação do solo extraordinariamente reduzida.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Espalhador • Cisterna móvel • Reboque

Version	STANDARD
Type	TL
Tyre Size	710/40 R 22.5
LI/SS	161 D/172 A8

Dimensions International Standard

Section Width (mm)	727
Overall Diameter (mm)	1140
Static Loaded Radius (mm)	514
Rolling Circumference (mm)	3490
SRI (mm)	550
Rim Rec	AG 24.00
ECE	E11-106R-003016

Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1350	1540	1730	2150	2445	2825	3200	3495	3835	4210
65	1480	1690	1900	2360	2685	3100	3515	3840	4210	4625
50	1795	2050	2300	2860	3250	3755	4260	4650	5100	5600
40	2020	2305	2585	3215	3655	4225	4790	5230	5735	6300
30	2240	2555	2865	3565	4055	4680	5310	5800	6360	6985
25	2340	2670	3000	3730	4240	4900	5560	6070	6655	7310
10	2665	3040	3415	4250	4830	5580	6330	6910	7580	8325

Printed on 18/05/2024 23:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..