

## XL GRIP (L3) - Especificações técnicas



### Description

XL GRIP (E-3/L-3) é um pneu de lonas cruzadas de base larga (wide), concebido para carregadores, com vista a minimizar o risco de cortes e perfurações nas aplicações pesadas de carga. O pneu assegura uma tração excelente, bem como um ciclo de vida prolongado do produto.

### UM

International Standard

### Construction

❖ BIAS

### Machinery

Industrial: Carregadora

OTR: Trator de esteira • Carregadora

Version	STANDARD
Type	TL
Tyre Size	29.5 - 25

## Dimensions International Standard

Ply Rating	28
Overall Width (mm)	760
Overall Diameter (mm)	1860
Static Loaded Radius (mm)	849
Rolling Circumference (mm)	5544
Rim Rec	25.00/3.5
TRA Code	L3

## Load capacity (Kg)

km/h / bar	4.25
10	17500

Printed on 18/05/2024 19:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..