

AGRIMAX RT 600 - Specificații tehnice

Descriere

AGRIMAX RT 600 este anvelopa ideală pentru pajiști, recoltare și împrăștiere. Datorită suprafeței mari de contact, AGRIMAX RT 600 asigură o distribuție excelentă a presiunii pe sol, reducând deteriorarea pajiștilor și protejând solul. Datorită tehnologiei de muchie rotundă, talonului ranforsat și numărului crescut de caneluri, garantează o stabilitate și tracțiune deosebite.

UM

US Standard

Construcție

 RADIAL

Mașinării

Agricultură: Mașină de recoltare • Mașină de împrăștiat • Tractor



Versiune	STEEL BELTED
Tip	TL
Dimensiunea anvelopei	IF 1250/50 R 32 CFO
LI/SS	201 B

Dimensiuni US Standard

Usa code	94070763
Lățimea secțiunii (inch)	49.1
Overall Diameter (inch)	81.2
Static Loaded Radius (inch)	35.3
Rolling Circumference (inch)	241.6
Rim Rec	VA44/1.7 (multipiece)
ECE	E11-106R-006958

Load capacity (lbs)

mph / psi	12	15	20	23	29	35	41	46	49	55
30	14380	16300	20460	22700	25250	27170	29730	31970	---	---
25	15690	17780	22310	24750	27530	29620	32140	34840	---	---
20	16790	19020	23870	26480	29460	31700	34690	37290	---	---
5 LT	21020	23820	29890	33160	36890	39690	43430	46690	---	---
5 HT	16790	18020	23870	26480	29460	31700	34690	37290	---	---
Upto 5 Cyc with front loader	---	26370	33770	37020	42950	47100	51540	55980	56880	59230

* For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Imprimat pe 5/18/2024 5:28 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..