

XL GRIP (L3) - Fișa de date



Descriere

XL GRIP (E-3/L-3) este o anvelopă cu cută înclinată cu bază lată pentru încărcătoare, concepută pentru a minimiza tăieturile și perforările în aplicațiile de încărcare dificile. Oferă tracțiune excepțională, precum și o durată de viață extinsă a anvelopei.

UM

Standard internațional

Construcție

 BIAS

Mașinării

Industrial: Încărcător

OTR: Buldozer • Încărcător

| SIZE | Version | TRA Code | PR | RIM REC | RIM ALT | OW | OD | SLR | RC | Type |
|--------------|------------------|----------|----|-----------|----------------|-----|------|-----|------|------|
| 16.0/70 - 20 | STANDARD | L3 | 16 | 13 SDC | | 405 | 1090 | 480 | 3295 | TL |
| 15.5 - 25 | STANDARD | E3/L3 | 12 | 12.00/1.3 | 12.00/1.3 (DC) | 402 | 1285 | 573 | 3767 | TL |
| 17.5 - 25 | DUAL BEAD | E3/L3 | 20 | 14.00/1.5 | | 435 | 1345 | 622 | 3980 | TT |
| 17.5 - 25 | DUAL BEAD | E3/L3 | 24 | 14.00/1.5 | | 435 | 1345 | 622 | 3980 | TL |
| 17.5 - 25 | DUAL BEAD | E3/L3 | 20 | 14.00/1.5 | | 435 | 1345 | 622 | 3980 | TL |
| 17.5 - 25 | STANDARD | E3/L3 | 12 | 14.00/1.5 | | 435 | 1345 | 622 | 3980 | TL |
| 17.5 - 25 | STANDARD | E3/L3 | 16 | 14.00/1.5 | | 435 | 1345 | 622 | 3980 | TL |
| 17.5 - 25 | STANDARD | E3/L3 | 20 | 14.00/1.5 | | 435 | 1345 | 622 | 3980 | TL |
| 20.5 - 25 | STANDARD | E3/L3 | 12 | 17.00/2.0 | | 530 | 1485 | 682 | 4395 | TL |
| 20.5 - 25 | STANDARD | E3/L3 | 16 | 17.00/2.0 | | 530 | 1485 | 682 | 4395 | TL |
| 20.5 - 25 | STANDARD | E3/L3 | 20 | 17.00/2.0 | | 530 | 1485 | 682 | 4395 | TL |
| 20.5 - 25 | STANDARD | E3/L3 | 24 | 17.00/2.0 | | 530 | 1485 | 682 | 4395 | TL |
| 23.5 - 25 | ARAMID BELTED HD | E3/L3 | 24 | 19.50/2.5 | | 600 | 1625 | 742 | 4810 | TL |
| 23.5 - 25 | STANDARD | E3/L3 | 16 | 19.50/2.5 | | 600 | 1625 | 742 | 4810 | TL |
| 23.5 - 25 | STANDARD | E3/L3 | 20 | 19.50/2.5 | | 600 | 1625 | 742 | 4810 | TL |
| 23.5 - 25 | STANDARD | E3/L3 | 24 | 19.50/2.5 | | 600 | 1625 | 742 | 4810 | TL |
| 26.5 - 25 | STANDARD | L3 | 20 | 22.00/3.0 | | 680 | 1740 | 796 | 5150 | TL |
| 26.5 - 25 | STANDARD | L3 | 28 | 22.00/3.0 | | 680 | 1740 | 796 | 5150 | TL |
| 26.5 - 25 | STANDARD | L3 | 32 | 22.00/3.0 | | 680 | 1740 | 796 | 5150 | TL |
| 29.5 - 25 | STANDARD | L3 | 28 | 25.00/3.5 | | 760 | 1860 | 849 | 5544 | TL |
| 29.5 - 25 | STANDARD | L3 | 32 | 25.00/3.5 | | 760 | 1860 | 849 | 5544 | TL |

Imprimat pe 5/18/2024 10:46 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..