

EARTHMAX SR 35 - Технические спецификации



Description

EARTHMAX SR 35 - это радиальная низкопрофильная шина с цельным металлокордом, специально разработанная для самосвалов с шарнирно-сочлененной рамой и колесных погрузчиков. Она идеально подходит для работ, требующих высоких тяговых характеристик и отличной проходимости. Шина Earthmax SR 35 обеспечивает транспортному средству великолепную тягу и устойчивость. Благодаря прочному каркасу с металлокордными брекерными слоями она обладает поразительно долгим сроком службы и стойкостью к сколам и проколам. Шина предлагается со стойкой к порезам резиновой смесью, что обеспечивает ей максимально возможный срок службы, какими бы суровыми ни были условия эксплуатации.

UM

US Standard

Construction

 RADIAL

Machinery

Производство: Шарнирно-сочлененный самосвал •
Бульдозер • Погрузчик

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	775/65 R 29
LI/SS	195 B/206 A2

Dimensions US Standard

Usa code	94064410
TMPH	151
Overall Width (inch)	30.5
Overall Diameter (inch)	69
Static Loaded Radius (inch)	31
Rolling Circumference (inch)	209.1
Rim Rec	24.00/3.5
Rim Alt	24.00/3.0, 25.00/3.5
Star Rating	**/*
TRA Code	E3/L3

Load capacity (lbs)

mph / psi	58	62	65	69
30	24000	24700	26000	26800
5	33100	34200	36400	37500

Printed on 19.05.2024 4:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..