

EARTHMAX SR 468 - Технические спецификации



Description

EARTHMAX SR 468 — это радиальные шины с цельным металлокордом, специально разработанные для карьерных самосвалов с жесткой рамой. Благодаря уникальному рисунку протектора эти шины, изготовленные с применением специальной резиновой смеси, идеально подходят для эксплуатации на твердых и скалистых грунтах и в суровых условиях горнодобывающих предприятий. Блоки протектора, формирующие грунтозацепы, с продольными канавками и пересекающимися блоками, способствуют рассеиванию тепла. Кроме того, упрочненная прямоугольная плечевая зона гарантирует выталкивание осколков камней из пятна контакта шины во избежание повреждений. EARTHMAX SR 468 была разработана с использованием новейшей технологии BKT, благодаря которой шина может выдерживать повышенную нагрузку. Она отличается долгим сроком службы и сопротивляемостью порезам и проколам от скальных пород.

UM

International Standard

Construction

 RADIAL

Machinery

Производство: Самосвал с жесткой рамой

Version	STANDARD COMPOUND
Type	TL
Tyre Size	37.00 R 57
LI/SS	245 B

Dimensions International Standard

TKPH	850
Overall Width (mm)	1030
Overall Diameter (mm)	3425
Static Loaded Radius (mm)	1520
Rolling Circumference (mm)	10315
Rim Rec	27.00/6.0
Rim Alt	29.00/6.0
Star Rating	**
TRA Code	E4

Load capacity (Kg)

km/h / bar	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	43750	45000	46250	47500	48750	50000	51500

Printed on 18.05.2024 22:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..