

EARTHMAX SR 468 - Технические спецификации



Description

EARTHMAX SR 468 — это радиальные шины с цельным металлокордом, специально разработанные для карьерных самосвалов с жесткой рамой. Благодаря уникальному рисунку протектора эти шины, изготовленные с применением специальной резиновой смеси, идеально подходят для эксплуатации на твердых и скалистых грунтах и в суровых условиях горнодобывающих предприятий. Блоки протектора, формирующие грунтозацепы, с продольными канавками и пересекающимися блоками, способствуют рассеиванию тепла. Кроме того, упрочненная прямоугольная плечевая зона гарантирует выталкивание осколков камней из пятна контакта шины во избежание повреждений. EARTHMAX SR 468 была разработана с использованием новейшей технологии BKT, благодаря которой шина может выдерживать повышенную нагрузку. Она отличается долгим сроком службы и сопротивляемостью порезам и проколам от скальных пород.

UM

International Standard

Construction

 RADIAL

Machinery

Производство: Самосвал с жесткой рамой

Version	STANDARD COMPOUND
Type	TL
Tyre Size	46/90 R 57
LI/SS	252 B

Dimensions International Standard

TKPH	980
Overall Width (mm)	1140
Overall Diameter (mm)	3575
Static Loaded Radius (mm)	1590
Rolling Circumference (mm)	10800
Rim Rec	29.00/6.0
Rim Alt	32.00/6.0
Star Rating	**
TRA Code	E4

Load capacity (Kg)

km/h / bar	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	53000	54500	56000	58000	60000	61500	63000

Printed on 18.05.2024 17:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..