

## TR 387 IND - Технические спецификации



### Description

TR 387 IND — индустриальные шины, предназначенные для промышленных прицепов и уплотнительной техники и отличающиеся высокой грузоподъемностью. Они предлагаются в различных версиях в зависимости от требований пользователя относительно устойчивости к порезам и разрывам, сложности условий эксплуатации и долговечности шин. Версия «Dual Bead» особенно хорошо подходит для промышленных тракторов и прицепов, которые используются в грузовых перевозках.

### UM

International Standard

### Construction

❖ BIAS

### Machinery

Производство: уплотнительная техника • Трактор-тягач •  
Прицеп

Version	DUAL BEAD
Type	TL
Tyre Size	620/75 - 30 (23.1 - 30)
LI/SS	161 A6

## Dimensions International Standard

Ply Rating	16
Section Width (mm)	605
Overall Diameter (mm)	1675
Rim Rec	DW 20 A ; DW 20 B
TRA Code	R3

## Load capacity (Kg)

km/h / bar	2.30
30	4625

Printed on 18.05.2024 17:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..