

TR 387 IND - Технические спецификации



Description

TR 387 IND — индустриальные шины, предназначенные для промышленных прицепов и уплотнительной техники и отличающиеся высокой грузоподъемностью. Они предлагаются в различных версиях в зависимости от требований пользователя относительно устойчивости к порезам и разрывам, сложности условий эксплуатации и долговечности шин. Версия «Dual Bead» особенно хорошо подходит для промышленных тракторов и прицепов, которые используются в грузовых перевозках.

UM

US Standard

Construction

❖ BIAS

Machinery

Производство: уплотнительная техника • Трактор-тягач • Прицеп

Version	DUAL BEAD HD
Type	TL
Tyre Size	620/75 - 30 (23.1 - 30)
LI/SS	160 A8

Dimensions US Standard

Usa code	94065325
Ply Rating	18
Section Width (inch)	23.8
Overall Diameter (inch)	65.9
Rim Rec	DW 20 A ; DW 20 B
TRA Code	R3

Load capacity (lbs)

mph / psi	38
25	11000

Printed on 18.05.2024 19:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..