

AGRIMAX RT 600 - Tekniska specifikationer

Description

AGRIMAX RT 600 är ett idealiskt däck för gräsmark, skörde- och spridningsarbeten. Den stora kontaktytan hos AGRIMAX RT 600 säkerställer utmärkt tryckfördelning mot marken, minskar skadorna på gräsmark och skyddar marken. Tack vare tekniken med rundad däckskuldra, förstärkt vulst och fler däckklackar uppnås fantastisk stabilitet och dragförmåga.

UM

US Standard

Construction

 RADIAL

Machinery

Lantbruk: Skördemaskin • Spridare • Traktor



Version	STANDARD
Type	TL
Tyre Size	710/70 R 38
LI/SS	178 D/181 A8

Dimensions US Standard

Usa code	94063420
Section Width (inch)	27.8
Overall Diameter (inch)	77.1
Static Loaded Radius (inch)	34.7
Rolling Circumference (inch)	233.3
Rim Rec	DW 23 B
Rim Alt	DW 25 B
ECE	E11-106R-006178

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35	41	46
40	6450	7640	8760	9750	10910	11900	13060	14050	15380	16530
30	6780	7990	9200	10250	11460	12500	13720	14760	16150	17360
25	7100	8370	9640	10740	12000	13090	14370	15460	16920	18190
20	7420	8750	10090	11220	12550	13690	15020	16170	17690	19010
5 LT	8640	10200	11750	13070	14630	15960	17500	18840	20610	22160
5 HT	7420	8750	10090	11220	12550	13690	15020	16170	17690	19010

Printed on 5/19/2024 4:57 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..