

AGRIMAX RT 600 - Tekniska specifikationer

Description

AGRIMAX RT 600 är ett idealiskt däck för gräsmark, skörde- och spridningsarbeten. Den stora kontaktytan hos AGRIMAX RT 600 säkerställer utmärkt tryckfördelning mot marken, minskar skadorna på gräsmark och skyddar marken. Tack vare tekniken med rundad däckskuldra, förstärkt vulst och fler däckklackar uppnås fantastisk stabilitet och dragförmåga.

UM

US Standard

Construction

 RADIAL

Machinery

Lantbruk: Skördemaskin • Spridare • Traktor



| | |
|-----------|-------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 750/65 R 26 |
| LI/SS | 171 A8/B |

Dimensions US Standard

| | |
|------------------------------|-------------------|
| Usa code | 94064311 |
| Section Width (inch) | 29.5 |
| Overall Diameter (inch) | 64.4 |
| Static Loaded Radius (inch) | 29 |
| Rolling Circumference (inch) | 196.3 |
| Rim Rec | DW 24 B |
| Rim Alt | DW 23 B ; DW 25 B |
| ECE | E11-106R-006182 |

Load capacity (lbs)

| mph / psi | 12 | 15 | 17 | 20 | 23 | 29 | 35 | 41 | 46 | 49 | 55 |
|-----------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 6240 | 7190 | 8130 | 8820 | 9630 | 10710 | 11530 | 12610 | 13560 | - | - |
| 25 | 6240 | 7190 | 8130 | 8820 | 9630 | 10710 | 11530 | 12610 | 13560 | - | - |
| 20 | 6680 | 7700 | 8720 | 9450 | 10320 | 11470 | 12350 | 13500 | 14520 | - | - |
| 5 LT | 8370 | 9630 | 10910 | 11820 | 12910 | 14360 | 15450 | 16910 | 18180 | - | - |
| 5 HT | 6680 | 7700 | 8720 | 9450 | 10320 | 11470 | 12350 | 13500 | 14520 | - | - |
| 5 Cyc | - | 11550 | 13070 | 14160 | 15460 | 17220 | 18520 | 20260 | 21780 | 22130 | 23050 |

Printed on 5/19/2024 3:20 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..