

AGRIMAX RT 600 - Tekniska specifikationer

Description

AGRIMAX RT 600 är ett idealiskt däck för gräsmark, skörde- och spridningsarbeten. Den stora kontaktytan hos AGRIMAX RT 600 säkerställer utmärkt tryckfördelning mot marken, minskar skadorna på gräsmark och skyddar marken. Tack vare tekniken med rundad däckskuldra, förstärkt vulst och fler däckklackar uppnås fantastisk stabilitet och dragförmåga.

UM

US Standard

Construction

 RADIAL

Machinery

Lantbruk: Skördemaskin • Spridare • Traktor



Version	STANDARD
Type	TL
Tyre Size	750/70 R 26
LI/SS	172 A8/B

Dimensions US Standard

Usa code	94073146
Section Width (inch)	30.7
Overall Diameter (inch)	68.9
Static Loaded Radius (inch)	30.9
Rolling Circumference (inch)	207.4
Rim Rec	DW 25 B
Rim Alt	DW 24 B
ECE	E11-106R-007934

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35	41	46	52
30	5970	6940	7930	8900	9780	10840	11950	12640	13890	-	-
25	5970	6940	7930	8900	9780	10840	11950	12640	13890	-	-
20	6400	7440	8490	9520	10570	11610	12800	13550	14880	-	-
5 LT	8010	9310	10630	11930	13230	14540	16030	16950	18630	-	-
5 HT	6400	7440	8490	9520	10570	11610	12800	13550	14880	-	-
5 Cyc	-	11170	12730	14290	15850	17420	19200	20310	22320	22670	23610

Printed on 5/19/2024 6:08 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..