



MULTIMAX MP 522 - Ladda ned faktablad



Description

MULTIMAX MP 522 är BKT:s flerfunktionsdäck utvecklat för industriella lantbrukstillämpningar. Det lämpar sig för alla lyft- och lastarbeten med fordon som teleskoplastare och kompakthjullastare. Stabilitet och dragförmåga är däckets styrkor, liksom enastående hållbarhet. Tack vare den speciella gummiblandningen har MULTIMAX MP 522 otrolig motståndskraft mot skärande underlag och punkteringar.

UM

International Standard

Construction

 RADIAL

Machinery

Lantbruk: Kompakthjullastare • Teleskoplastare
Industri: Kompakthjullastare • Teleskoplastare

| SIZE | Version | LI/SS | RIM REC | RIM ALT | SW | OD | SLR | RC | SRI | Type | ECE |
|---|----------|----------|--------------------|--|-----|------|-----|------|-----|------|-----------------|
| 280/80 R 18 IND (10.5/80 R 18) | STANDARD | 132 A8/B | W 9 ; 9 ; 9 SDC | W 8 ; W 10 | 282 | 907 | 421 | 2748 | 425 | TL | E11-106R-002962 |
| 340/80 R 18 IND (12.5/80 R 18) | STANDARD | 143 A8/B | 11 ; 11 SDC ; W 11 | W 10 ; 12 ; 12 SDC | 343 | 1006 | 458 | 3023 | 475 | TL | E4-106R-002654 |
| 340/80 R 20 IND | STANDARD | 144 A8/B | 11 | W10 ; 11 SDC ; W11 ; 12 ; 12 SDC | 343 | 1052 | 481 | 3212 | 500 | TL | E11-106R-002969 |
| 380/75 R 20 IND (14.5 R 20) | STANDARD | 148 A8/B | W 12 | W 11 ; 11 ; 12 | 384 | 1074 | 483 | 3251 | 500 | TL | E11-106R-002963 |
| 400/70 R 20 IND (16.0/70 R 20) | STANDARD | 149 A8/B | 13 | 12 SDC ; 13 SDC ; 14 | 404 | 1068 | 476 | 3199 | 525 | TL | E4-106R-002319 |
| 400/70 R 24 IND | STANDARD | 152 A8/B | 13 | DW 12 ; 13 SDC ; DW 13 ; DW 13 L ; DW 14 L | 404 | 1170 | 533 | 3527 | 575 | TL | E11-106R-002964 |
| 400/80 R 24 IND (16.0/80 R 24) | STANDARD | 162 A8/B | DW 13 | DW 12 ; DW 13 L ; DW 14 L | 404 | 1250 | 553 | 3778 | 600 | TL | E11-106R-002965 |
| 440/80 R 24 IND | STANDARD | 161 A8/B | DW 14 L | DW 13 ; DW 13 L ; DW 15 L | 441 | 1314 | 586 | 3958 | 625 | TL | E11-106R-002966 |
| 460/70 R 24 IND (17.5L R 24) | STANDARD | 159 A8/B | DW 15 L | DW 14 L ; DW 16 L | 465 | 1250 | 568 | 3766 | 600 | TL | E4-106R-002396 |
| 500/70 R 24 IND (19.5L R 24) | STANDARD | 164 A8/B | DW 16 L | DW 15 L ; DW 18 L | 503 | 1310 | 595 | 3940 | 625 | TL | E4-106R-002395 |
| 540/70 R 24 IND | STANDARD | 168 A8/B | DW 16 L | DW 18 L | 530 | 1366 | 611 | 4133 | 650 | TL | E11-106R-002967 |
| 480/80 R 26 IND | STANDARD | 160 A8/B | DW 15 L | DW 16 L | 479 | 1428 | 638 | 4287 | 675 | TL | E11-106R-002970 |
| 480/80 R 26 IND | STANDARD | 167 A8/B | DW 15 L | DW 16 L | 479 | 1428 | 638 | 4287 | 675 | TL | E11-106R-008146 |
| 440/80 R 28 IND | STANDARD | 156 A8/B | DW 14 L | DW 13 ; DW 13 L ; DW 15 L | 441 | 1415 | 643 | 4278 | 675 | TL | E11-106R-002968 |

Printed on 5/18/2024 9:56 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..