

RIDEMAX FL 693 M - Tekniska specifikationer



Description

RIDEMAX FL 693 M är det idealiska radialdäcket för användare som regelbundet kör på väg med släpvagn/tankbil. RIDEMAX FL 693 M är i själva verket designat för 75 procent användning på väg och erbjuder utmärkt vägprestanda genom att prioritera både komfort och självrensande egenskaper. Hastighetsindexklasserna D/E i serien imponerar med högre hastigheter vid körning på väg, vilket leder till betydande tidsbesparingar. Det låga rullningsmotståndet bidrar till lägre bränsleförbrukning, samtidigt som den förstärkta vulsten och stålbalten säkerställer extra hållbarhet.

UM

US Standard

Construction

 RADIAL

Machinery

Lantbruk: Tankbil • Släpvagn

Version	STANDARD
Type	TL
Tyre Size	580/65 R 22.5
LI/SS	166 D/163 E

Dimensions US Standard

Usa code	94037254
Section Width (inch)	22.7
Overall Diameter (inch)	52.2
Static Loaded Radius (inch)	22.5
Rolling Circumference (inch)	158.7
Rim Rec	AG 18.00
Rim Alt	AG 16.00 ; AG 17.00 ; AG 20.00
ECE	E4-106R-000804

Load capacity (lbs)

mph / psi	15	17	23	29	35	41	46	52	58
45	3980	4520	5380	6350	7260	8070	9030	9890	10750
40	4330	4920	5840	6900	7890	8760	9820	10760	11680
30	5240	5940	7080	8340	9560	10610	11880	13020	14140
25	5890	6680	7950	9380	10740	11930	13360	14630	15890
15	6830	7760	9240	10900	12470	13860	15510	16990	18460
5	7790	8840	10520	12410	14200	15770	17670	19360	21030

Printed on 5/18/2024 8:20 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..