

## AGRIMAX FORCE - Teknik Özellikler



### Description

BKT'nin lüks ürünü AGRIMAX FORCE, yüksek güçlü traktörler ve biçerdöverlerle toprak işleme, taşıma ve hasat uygulamaları için özel olarak tasarlanmış, üstün performans ve verimlilik sağlayan radyal bir lastiktir. IF teknolojisi sayesinde, bu lastik, standart bir lastiğe kıyasla daha düşük bir şişirme basıncıyla ağır yükler taşıyarak toprak sıkışmasını azaltır. AGRIMAX FORCE, güçlendirilmiş bir damağa sahiptir ve konforlu bir sürüş deneyimine ek olarak gelişmiş çekiş, üstün kendi kendini temizleme özellikleri ve yakıt ekonomisi sağlar.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Zirai: Biçerdöver • Yüksek güçte traktör

Version	STANDARD
Type	TL
Tyre Size	IF 800/70 R 42 CFO
LI/SS	186 D

## Dimensions US Standard

Usa code	94073641
Section Width (inch)	31.3
Overall Diameter (inch)	84.6
Static Loaded Radius (inch)	37.4
Rolling Circumference (inch)	252
Rim Rec	DW 27 B
Rim Alt	DW 25 B, DW 28 B, DW 30 B
ECE	E4-106R-002650
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
45	8950	10280	11810	13340	14860	16380	17910	19060
From 40 to 25	9840	11310	12980	14660	16340	18010	19690	20900
20	10230	11760	13500	15240	16990	18730	20470	21780
12	10630	12210	14020	15830	17640	19440	21250	22620
5	12500	14360	16490	18620	20740	22870	25000	26600
Upto 20 Cyc	12790	14690	16880	19060	21230	23410	25580	27230
Upto 10 Cyc	15260	17530	20120	22720	25320	27910	30510	32460
Upto 5 Cyc	16730	19220	22070	24920	27770	30610	33460	35600
5HT	10230	11760	13500	15240	16990	18730	20470	21780

Printed on 5/18/2024 9:19 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..