

## AGRIMAX RT 600 - Teknik Özellikler

### Description

AGRIMAX RT 600; çim saha, hasat ve yayma uygulamaları için ideal bir lastiktir. Geniş temas alanı sayesinde AGRIMAX RT 600, arazide mükemmel bir basınç dağılımı sağlayarak çim sahadaki hasarı azaltır ve toprağınızı korur. Yuvarlak omuz teknolojisi, güçlendirilmiş damak ve daha yüksek diş sayısı sayesinde mükemmel sabitleme ve çekiş sağlar.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Zirai: Biçerdöver • Yayıcı • Traktör



Version	STANDARD
Type	TL
Tyre Size	620/75 R 26 (23.1 R 26)
LI/SS	167 A8/B

## Dimensions US Standard

Usa code	94050444
Section Width (inch)	24.6
Overall Diameter (inch)	62.6
Static Loaded Radius (inch)	28.7
Rolling Circumference (inch)	191
Rim Rec	DW 20 B
ECE	E11-106R-002993

## Load capacity (lbs)

mph / psi	12	15	20	23	29	35	41	46	49	55
30	5530	6370	7810	8530	9380	10220	11060	12010	-	-
25	5530	6370	7810	8530	9380	10220	11060	12010	-	-
20	5920	6820	8370	9140	10040	10930	11840	12860	-	-
5 LT	7420	8540	10470	11440	12570	13690	14830	16100	-	-
5 HT	5920	6820	8370	9140	10040	10930	11840	12860	-	-
5 Cyc.	-	9090	11650	12780	14810	16250	17780	19310	19610	20420

Printed on 5/19/2024 10:06 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..